








BraceFITTING

IP68 conduit protection for extreme conditions



Key features



High protection as standard: All variants of the non-metallic BraceFITTING offer IP68 protection.



Strain resilience: Integrated strain relief.



Twice the security: The directly injected O-ring ensures secure installation and perfect sealing properties.



Time saving:One-piece construction that fits all.





Fitting options



BraceFITTING





BraceFITTING with metal connecting thread (swivel)



BraceFITTING with 45° angle



BraceFITTING with 90° angle



BraceFITTING with standard cable gland (swivel)



BraceFITTING with cable gland for EMC protection (swivel)



BraceFITTING with VentGLAND®







BraceFITTING Adaptor

BraceFITTING Y-Connector

BraceFITTING T-Connector

Technical data











Protection class	IP68
Temperature range	-40 °C - 100 °C
Material Fitting	Polyamide UL94 - V0, Gasket: TPU
Sizes	M12, M16, M20, M25, M32, M40, M50 & M63
Colours	

BraceFITTING is used in these industries



Rail Industry



Automation



Shipbuilding



Wind Industry



Machine & Plant Engineering



Chemical Industry



Electrical Installation



This leaflet is AR enabled.





Download the free Zappar App.



Scan the target to unlock the content



contact@wiska.de www.wiska.com

BraceFITTING 03/2020